

Augers

For skid-steer loaders, compact tractors, mini compact loaders, excavators, mini excavators, tractor loader backhoes and telehandlers



PALADIN LIGHT CONSTRUCTION

FEATURES:

- 5 to 60 GPM available
- augers available up to 48" diameter
- wide variety of auger diameters, lengths and style for every digging application
- extensions available for deeper digging
- various mounts available for most applications
- planetary and chain reduction auger drives available
- 2 speed auger drive available
- 2 year warranty; up to 3 years additional planetary warranty



Augers

2 year warranty available

Rock Augers - Bullet Tooth Style

For solid, fracturable rock, frozen ground & compacted soils



Diameter		Tooth
IN	MM	QTY
6"	152	6
9"	229	8
10"	254	8
12"	305	12
16"	406	16
18"	457	18
20"	508	20
24"	610	24
30"	762	30
36"	914	36

Rock Auger Features:

- bullet style teeth
- fabricated boring head
- heavy duty single flighting
- 2" hexagon collar **ONLY**
- available in 4' length
- 3/4" thick bottom flight
- hardfaced outer edge

Agricultural PTO Augers

Designed to fit all PTO drive units with 2" round output shafts



Diameter		Tooth
IN	MM	QTY
6"	152	2
9"	229	2
12"	305	4
14"	325	5
18"	457	6
24" tree	610	9

Agricultural PTO Auger Features:

- fabricated boring head
- hardened bolt-on gage teeth (outside)
- hardened bolt-on wisdom teeth (inside)
- hardened fishtail point
- heavy-duty double flighting
- PTO augers available in 42"/48" length

Medium Duty - MDF Style Augers

For light to moderate ground conditions

MDF Auger Features:

- fabricated boring head
- outside bolt-on gage teeth & wisdom teeth
- standard or carbide teeth and point available
- heavy-duty, 5/16" thick flighting
- available with standard or carbide wear components
- heavy-duty center shaft, 3 3/4" tubing x 5/16" wall
- collars available in 2 1/2" hexagon and 2-5/8" hexagon



Heavy Duty - MDC Style Augers

For difficult ground conditions, compacted soils, heavy clay, asphalt, frozen ground & fracturable rock

MDC Auger Features:

- heavy-duty cast steel boring head
- outside drive-in gage teeth & inside wisdom teeth
- standard or carbide teeth and point available
- heavy-duty, 5/16" thick flighting
- available with standard or carbide wear components
- heavy-duty center shaft, 3 3/4" tubing x 5/16" wall
- collars available in 2 1/2" hexagon and 2-5/8" hexagon



Diameter		Flighting	Tooth	Overall
IN	MM	Length	QTY	Length
8"	203	40" or 60"	2	103"
9"	229	40" or 60"	2	103"
10"	254	40" or 60"	2	103"
12"	305	40" or 60"	4	103"
14"	325	40" or 60"	4	103"
16"	406	40" or 60"	4	103"
18"	457	40" or 60"	6	103"
20"	508	40" or 60"	6	103"
24"	610	40" or 60"	7	103"
30"	762	40" or 60"	8	103"
36"	914	40" or 60"	8	103"
42"	1067	40" or 60"	10	103"
48"	1219	40" or 60"	13	103"

Specifications and design are subject to change without notice and without liability, therefore, whenever applicable specifications are in accordance with SAE standards.