

# Root Rake



**PALADIN** LIGHT CONSTRUCTION



(Root Rake shown with optional winch)

## FEATURES

- available in 72", 78" and 84" for maximum efficiency
- upper push-bar, aggressive profiles with H&L-230 style teeth work together to neatly gather material into a more manageable pile
- zinc plated, greasable, pivot pins with protected grease zerks, and replaceable hardened steel bushings.
- weld-on D-ring for numerous applications
- 2- year limited warranty



# Root Rake

# SPECIFICATIONS

Root Rake	72"	78"	84"
A. grapple width	70"	70"	70"
B. rake width	72"	78"	84"
C. overall height	38"	38"	38"
D. grapple opening	49"	49"	49"
E. tooth position	25"	25"	25"
F. over length	27"	27"	27"
overall weight (lbs)	1,095	1,150	1,220
tine spacing	9½"	10"	8½"

  

Specifications and design are subject to change without notice and without liability therefore. Whenever applicable specifications are in accordance with SAE standards.

**B**radco's heavy duty Root Rake allows you to remove the toil and leave the soil at your job site with aggressive tine and grapple profiles that lock material in place and stabilize during transport. The leading edge of the grapple travels in a range of motion that pulls material into the bucket area to optimize its large capacity for brush and debris.

Bradco's Root Rake is constructed of high strength material with replaceable pin-on H&L-230 style teeth for durability, serviceability, and extended life. Expanded metal backing provides protection for cylinders while still allowing visibility to your work area.

More unique features include a pilot operated check for positive lock clamping, replaceable hardened steel bushings at all pivot locations and a weld-on D-ring for countless applications.